

HYLITE™
LED Lighting

NEXGEN
PRODUCTS

Available in Two Popular Lumen Packages
to suit a Variety of Flood Lighting Applications

• 170+ LpW • IP67 • Glare-Free, UGR <19

The Ultimate Flood Light for Versatility

AEON™
ECO SERIES

With Enhanced Glare-Free Illumination and various Beam Spreads, AEON ECO Series Flood Light Provides Crisp Illumination, avoiding any Visual Discomfort. AEON's Proprietary Optics produce Ideal Light Distribution and Beam Angles for a Variety of Flood Lighting applications, while saving you up to 79% in Energy use compared to Traditional Lighting.

Engineered with State-of-the-Art technology for Glare Control, and Uniform Illumination, AEON ECO Series Flood Light features Instant On/Off, Dimming, Full Controllability, High Energy Efficiency, Flicker-Free Lighting and Complete Flexibility.

AEON ECO Series Flood Light delivers a Simple, Smart and Easy-to-use Flood Lighting Solution to provide Advanced Functionality, Versatility and Operational Efficiency.

2 Popular Lumen Packages to Suit a Variety
of Indoor and Outdoor Applications:

310W: 51,150 Lumens

500W: 80,000 Lumens



Proprietary
& Patented
Designs!

The Most
Efficient &
Powerful LED
Flood Light in
the Industry!



Shown with Optional Tempered Glass Lens

Illuminating facts about High Performance AEON™ ECO Series LED Flood Light Better for your Eyes, Better for the Planet.

What makes the AEON™ LED Flood Light your Lighting Solution of Choice?

- The most powerful Flood Light Luminaire with the Highest Reliability Level: Incredibly High (95%+) Total Efficiency and with the Highest Efficacy in its own Class: Up to 170+ Delivered LpW. Greater Light, Fewer Luminaires.
- Heavy-duty, Lightweight and Durable Die-Cast Design for High Wear Resistance: Withstands Harsh, Extreme Outdoor Conditions and Corrosive Environments.
- Operational Flexibility: Adaptable to Various Intelligent Lighting Controls - Wired or Wireless, Wi-Fi, Zigbee, Dali, AirMesh, Hybrid Networked Lighting Controls, etc.
- Technology within the Luminaire: No Outside Exposure to any Sensitive Electronic Components. Offers Advanced Functionality and User Friendly features with Quick Connect Wiring System. No Manual Wiring Required for Dimming or Controls - Saving Time and Labor for Installation.
- High Color Rendition showing True Colors: CRI >85+.
- Excellent for 4K, Ultra-HD and HDTV Broadcasting, Digital Photography and Flicker-free, Slow-Motion Recording for Optimal Television and Security Viewing.
- Proprietary Glare-Free Illumination: No Visual Discomfort. UGR <19.
- Neighborhood-Friendly: Avoids Light Pollution and Trespass. Optical Accuracy - Directs Light precisely where needed without any Light Spillage or Sky Glow.
- Precise, Custom-engineered Optics with Controlled Intensity and Uniformity: Maintains Consistent Delivered Foot Candles over the Luminaires life with Minimal Lumen Depreciation.
- State-of-the-Art, Aesthetically Pleasing Compact Design with No Exposed Electronics or Wiring. Rugged, Weather-tight Design, IP67 Rated for Wet location.
- Proprietary Thermal Efficient Design with Passive Cooling Maximizes Heat Dissipation for Longer Life of the Luminaire. Designed for Greater Life Expectancy in Warmer Climates.
- Patented Cross-Vent Convection Design for Longer Life of LED Package and Electronics.
- Variable Dimming Control: 0-10VDC
- Ultra-Low EMI (THD <20) eliminates Electrical Interference with surrounding sensitive Electronic Systems.
- User Friendly Features: Lenses, Modules and Drivers are Field-Changeable. Saves Time, Labor and Money....no need to replace the entire Luminaire!
- Available with Optional Tempered Glass Lens for additional Safety and UV Protection



98%
RECYCLABLE

NO

LEAD, MERCURY, TOXIC
GASES OR HEAVY METALS

Additional Options available:

- Full RGB Colors and DMX Controls
- Extended Warranty
- Complete Package with Poles, Cross-Arms & Platforms

100%
Project
Financing
Available

Designed, Engineered &



Assembled in the USA

AEON Model	Watts	Delivered Lumens	HID Equivalent	Energy Savings*	Current Draw (mA)						Net Weight	EPA (Sq. Ft.)
					120V	208V	240V	277V	347V	480V		
HL-AEF-310WD HL-AEF-310WD-TG	310W	51,150	1500W	79%	2719	1569	1360	1243	993	718	23.5 lbs. (10.6 Kg.) 28 lbs. (12.5 Kg.)	1.3
HL-AEF-500WD HL-AEF-500WD-TG	500W	80,000	2000W	75%	4386	2530	2193	2006	1601	1157	24 lbs. (11 Kg.) 28.5 lbs. (13 Kg.)	1.3

TG = With Tempered Glass Lens


* Does not include Ballast Loss, Maintenance, Replacement Lamp Savings and Disposal Costs which amount to an additional Savings of 30~50%!

NEXGEN PRODUCTS

- Patented Revolutionary Aerodynamic Design for Minimal Wind Resistance.
- UV Stabilized Electrostatic Finish and Stainless Steel Hardware to withstand Extreme Outdoor Conditions.
- Incredibly Long Lifespan of over 100,000 Hours.
- Solid-State: No Moving Parts. Ideal for High Vibration Areas (ANSI C136.31, 3G Rated). Simple, Reliable, and Affordable, Maintenance-free Design.
- Advance Technology for Luminaire Longevity: Integrated Power Supply Operates at Lower Temperature and at incredible 95%+ Efficiency.
- 6kV (Line-Line) Surge Protection and 10kA / 20kV Inline Surge Protection against Over Voltage, Short Circuiting, and Over Temperature.
- Suitable for Ambient Temperatures: -40°F - +122°F (-40°C - +50°C).
- Adjustable in 7.5° Increments: 0-90° Orient and 270° Tilt Angle.
- Standard Included: Instant On/Off, Continuous Dimming, Prewired Sheathed Cord, Hoist Hook and 3.3 ft (1m) Stainless Steel Safety Cable.
- RoHS Compliant: No Lead, Mercury, Toxic Gases or any Hazardous Materials. Facilitates LEED® points.
- Environmentally Friendly: 98% Recyclable.
- Save Labor Cost Significantly: Quick & Easy Installation Process. Lowest Total Cost of Ownership. Shortest Payback Period and a High ROI.
- Several Mounting Options: Yoke, Pendant, Wire Loop or Hook.
- Meets/Exceeds National and International Standards

Standard LED Optics

SAVE UP TO
79%
ON YOUR
ENERGY COSTS



AEON™
Proprietary
Glare-Free
LED Optics



Shown with Optional Tempered Glass Lens

**2-for-1
Replacement**
More Light
Less
Luminaires

**Multi-Voltage
Options**
120-277VAC / 347-480VAC



98%
RECYCLABLE



NO
LEAD, MERCURY, TOXIC GASES
OR HEAVY METALS



As part of the company's continuous product improvement program, HyLite reserves the right to change materials or modify the design of its product without notification. All Specifications subject to change without notice. All values are design and/or typical values when measured under laboratory conditions. Actual Values depend upon the ambient temperature of the installation location. Please consult factory for your specific requirements.


© 2018-2025 HyLite LED, LLC., USA. All Rights Reserved. Aeon and the Products described in it are Copyrighted by HyLite LED, LLC., USA, with All Rights Reserved. This document may not be Copied in Whole or Part, without the Express Written Consent of HyLite LED, LLC., USA.

For more information, please visit: <https://aeonledlighting.com/>


051225



HL-AEF-310WD and HL-AEF-500WD Dimensions with Polycarbonate Lens



HL-AEF-310WD and HL-AEF-500WD Dimensions with Tempered Glass Lens



Ordering Nomenclature:

HL	—	AEF	—	310	—	5000	—	4	—	277V	—	WH	—	TG
COMPANY		SERIES		WATTS		CCT		NEMA SPREAD		VOLTAGE		COLOR		OPTIONS
				310WD 500WD		40K = 4000K 50K = 5000K		4 6		277V = 120V-277V 480V = 347V-480V		WH = White BZ = Bronze GY = Gray BK = Black		See Options, below

Important Note:

Standard CCT: 5000K
Other CCT'S available as
"Special Order" only and
with Longer Lead Times

Important Note:

Standard Color: Signal White. Other Colors
available as "Special Orders" only and with
Longer Lead Times

Options:

TG Tempered Glass

PCK-7 Photo Control Receptacle Kit Only (Photocell not included)